

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Ultrafill 3 Black**

Article number: 86801

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



health hazard

Carc. 2 H351 Suspected of causing cancer.



Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word **Danger**

Hazard-determining components of labelling:

4-methylpentan-2-one

Hazard statements

H222 Extremely flammable aerosol.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 1)

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-25%
CAS: 1332-58-7 EC number: 310-194-1	Kaolin substance with a Community workplace exposure limit	5-10%
CAS: 68476-85-7 EINECS: 270-704-2	Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)). ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	Butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	<5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	<5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

After inhalation Supply fresh air; consult doctor in case of symptoms.

After skin contact Instantly rinse with water.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Rinse out mouth.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained breathing apparatus.
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter drainage system, surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on flames or red-hot objects.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
Store in cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Protect from heat and direct sunlight.
Store container in a well ventilated position.
- **Storage class 2 B**
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

· **Components with limit values that require monitoring at the workplace:**

115-10-6 Dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 3)

108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm
 Long-term value: 208 mg/m³, 50 ppm
 Sk, BMGV

1332-58-7 Kaolin

WEL Long-term value: 2 mg/m³

68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).

WEL Short-term value: 2180 mg/m³, 1250 ppm
 Long-term value: 1750 mg/m³, 1000 ppm
 Carc (if LPG contains > 0.1% of buta-1.3-diene)

78-93-3 Butanone

WEL Short-term value: 899 mg/m³, 300 ppm
 Long-term value: 600 mg/m³, 200 ppm
 Sk, BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
 Long-term value: 274 mg/m³, 50 ppm
 Sk

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
 Long-term value: 724 mg/m³, 150 ppm

Regulatory information WEL: EH40/2020

DNELs**115-10-6 Dimethyl ether**

Inhalative Long term systemic effect 1,894 mg/m³ (Worker)

67-64-1 Acetone

Dermal Long term systemic effect 186 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 1,210 mg/m³ (Worker)
 Acute local effect 2,420 mg/m³ (Worker)

108-10-1 4-methylpentan-2-one

Dermal Long term systemic effect 11.8 mg/kg/day (Worker)
 Inhalative Long term systemic effect 83 mg/m³ (Worker)
 Acute local effect 208 mg/m³ (Worker)
 Long term local effect 83 mg/m³ (Worker)
 Acute systemic effect 208 mg/m³ (Worker)

78-93-3 Butanone

Dermal Long term systemic effect 1,161 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 600 mg/m³ (Worker)

108-65-6 2-methoxy-1-methylethyl acetate

Dermal Long term systemic effect 796 mg/kg/day (Worker)
 Inhalative Long term systemic effect 275 mg/m³ (Worker)
 Long term local effect 550 mg/m³ (Worker)

123-86-4 n-butyl acetate

Dermal Acute systemic effect 11 mg/kg bw/day (Worker)
 Long term systemic effect 11 mg/kg bw/day (Worker)
 Inhalative Long term systemic effect 300 mg/m³ (Worker)
 Acute local effect 600 mg/m³ (Worker)
 Long term local effect 300 mg/m³ (Worker)
 Acute systemic effect 600 mg/m³ (Worker)

1333-86-4 Carbon black

Inhalative Long term systemic effect 2 mg/m³ (Worker)
 Long term local effect 2 mg/m³ (Worker)

78-83-1 Butanol

Inhalative Long term local effect 310 mg/l (Worker)

100-41-4 ethylbenzene

Dermal Long term systemic effect 180 mg/kg/day (Worker)
 Inhalative Acute local effect 293 mg/m³ (Worker)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 5)

	0.1 mg/l (Aqua (marine water))
1330-20-7 xylene	
PNEC	0.327 mg/l (Aqua (freshwater)) 0.327 mg/l (Aqua (marine water)) 12.46 mg/l (Freshwater sediment) 12.46 mg/l (Marine water sediment) 6.58 mg/l (Sewage treatment plant) 2.31 mg/kg (Soil)
Ingredients with biological limit values:	
108-10-1 4-methylpentan-2-one	
BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
78-93-3 Butanone	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Only during spraying without adequate removal by suction.

Filter AX (EN 14387)

· **Hand protection**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses (EN 166)

Tightly sealed safety glasses. (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 6)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Aerosol
Colour:	Grey
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	Not applicable, as aerosol
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.4 Vol %
Upper:	26.2 Vol %
Flash point:	Not applicable, as aerosol
Ignition temperature:	226 °C
Decomposition temperature:	Not determined.
pH	Mixture is non-polar/aprotic.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Not miscible / difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	513 - 1760 kPa
Density and/or relative density	
Density	Not determined
Relative density at 20 °C	0.8
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	662 g/l VOC
Change in condition	
Evaporation rate	Not applicable.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 7)

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.
- **10.5 Incompatible materials:** Oxidizing agents
- **10.6 Hazardous decomposition products:**
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

67-64-1 Acetone

Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	20,000 mg/kg (Rabbit)

108-10-1 4-methylpentan-2-one

Oral	LD50	2,100 mg/kg (Rat)
Dermal	LD50	16,000 mg/kg (Rabbit)

78-93-3 Butanone

Oral	LD50	3,300 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rabbit)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,500 mg/kg (Rat)
------	------	-------------------

123-86-4 n-butyl acetate

Oral	LD50	14,000 mg/kg (Rat)
------	------	--------------------

1333-86-4 Carbon black

Oral	LD50	10,000 mg/kg (Rat)
------	------	--------------------

78-83-1 Butanol

Oral	LD50	2,460 mg/kg (Rat)
Dermal	LD50	4,200 mg/kg (Rabbit)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (Rat)
Dermal	LD50	5,000 mg/kg (Rabbit)

108-90-7 chlorobenzene

Oral	LD50	2,910 mg/kg (Rat)
------	------	-------------------

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)

64742-95-6 Hydrocarbons, C9, aromatics

Oral	LD50	>6,800 mg/kg (Rat)
Dermal	LD50	>3,400 mg/kg (Rabbit)

- **Serious eye damage/irritation** Causes serious eye irritation.

- **Carcinogenicity** Suspected of causing cancer.

· **11.2 Information on other hazards**

- **Endocrine disrupting properties**

78-93-3	Butanone
---------	----------

List II

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 8)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

115-10-6 Dimethyl ether

EC50 (48 hr)	>4,000 mg/l (Daphnia magna)
EL50 (48 hr)	4,001 mg/l (Daphnia magna)
LC50 (48 hr)	755,549 mg/l (Daphnia magna)
LC50 (96 hr)	154.9 mg/l (Algae)
	4,001 mg/l (Poecilia reticulata)

67-64-1 Acetone

EC50	61,150 mg/l (Activated sludge) (30 mins)
EC50 (48 hr)	39 mg/l (Daphnia magna)
LC50 (96 hr)	8,300 mg/l (Fish)
	5,540 mg/l (Oncorhynchus mykiss)
NOEC (28 days)	2,212 mg/l (Daphnia magna)

108-10-1 4-methylpentan-2-one

EC50 (48 hr)	>200 mg/l (Crustacea)
LC50 (96 hr)	>179 mg/l (Fish)

68476-85-7 Petroleum gases, liquefied (contains less than 0.1 % w/w 1,3-butadiene (EINECS No 203-450-8)).

EC50 (96 hr)	12.32 mg/l (Algae) ((Q)SAR calculation method)
LC50 (48 hr)	69.43 mg/l (Daphnia magna) ((Q)SAR calculation method)
LC50 (96 hr)	49.47 mg/l (Fish) ((Q)SAR calculation method)

78-93-3 Butanone

EC50 (48 hr)	308 mg/l (Daphnia magna)
LC50 (96 hr)	2,993 mg/l (Pimephales promelas)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 (48 hr)	>100 mg/l (Crustacea)
EC50 (72 hr)	>100 mg/l (Algae)
LC50 (96 hr)	>100 mg/l (Fish)
NOEC	100 mg/l (Crustacea)
	>10 mg/l (Fish)

123-86-4 n-butyl acetate

EC50 (48 hr)	44 mg/l (Daphnia magna)
EC50 (72 hr)	674.7 mg/l (Desmodesmus subspicatus)
LC50 (48 hr)	44 mg/l (Daphnia magna)
LC50 (96 hr)	18 mg/l (Pimephales promelas)
NOEC (72 hr)	200 mg/l (Desmodesmus subspicatus)

1333-86-4 Carbon black

EC50 (24 hr)	>5,600 mg/l (Daphnia magna) (OECD 202)
LC50 (96 hr)	>1,000 mg/l (Brachydanio rerio) (OECD 203)

78-83-1 Butanol

CE10 (16 hr)	750 mg/l (Pseudomonas Putida) (Bacteria: CE10)
CE50 (15 mins)	1,225 mg/l (Photobacterium phosphoreum) (Bacteria: Microtox Test: long term toxicity)
CI 50 (48 hr)	1,439 mg/l (Daphnia magna) ((DIN 38412))
CL50	1,430 mg/l (Pimephales promelas) (96 hours)
EC50 (48 hr)	1,100 mg/l (Daphnia magna)
EC50 (72 hr)	1,799 mg/l (Selenastrum capricornutum)
EL50 (48 hr)	885 mg/l (Leuciscus Idus) (CLO, 48 h (DIN 38412))
LC50 (96 hr)	1,430 mg/l (Pimephales promelas)
NOEC	>1,000 mg/l (Activated sludge)
NOEC (21 days)	20 mg/l (Daphnia magna)

100-41-4 ethylbenzene

EC50	>100 mg/l (Daphnia magna)
LC50 (96 hr)	>10 mg/l (Fish)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 9)

1330-20-7 xylene

CE50	10 mg/l (Fish) (72h)
EC50 (48 hr)	7.4 mg/l (Daphnia magna)
LC50 (96 hr)	3.77-13.5 mg/l (Fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
- Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.
- **Label** 2.1
- **IMDG, IATA**
- 
- **Class** 2.1 Gases.
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Gases.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 10)

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
NK	65.5

- **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H220 Extremely flammable gas.
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H280 Contains gas under pressure; may explode if heated.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H336 May cause drowsiness or dizziness.
 - H351 Suspected of causing cancer.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- **Department issuing data specification sheet:** Environment protection department

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.01.2023

Version number 3 (replaces version 2)

Revision: 19.01.2023

Trade name: Ultrafill 3 Black

(Contd. of page 11)

Abbreviations and acronyms:

RID: (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 : Aerosols – Category 3
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Data compared to the previous version altered. *

GB